



Weighing indicator (built-in printer)

Features

- Up to 1/30,000 display resolution (Internal resolution 1/600,000)
- Weighing units available in kg, g, lb and viss
- Digital calibration
- Dual range model available: multi range or multi interval
- Preset weight or quantity; Pre-tare; Weight accumulation; Check mode Hi / OK / Lo
- Simple counting; Gross / Net indication; Hold function; Animal scale function
- Built-in mini printer (date and time available)



Specifications

Operation Temperature: 0°C ~ 40°C (32°F ~ 104°F)
Power Supply: 110/220VAC (±15%) + DC 6V/4Ah Rechargeable Battery
Dimensions: 276 X 172 X 153mm (L x W x H) 276 X 202 X 153mm (L x W x H)(Including double-sided display)
Display: LCD, 6 Digits, 25 mm (Height), LED backlight
Net Weight: ~ 2.25kg

[Printer]

Print Characters: English / Traditional Chinese (16 English characters per one line)
Printer Head Reliability: MCBF 10X10 ⁵ lines
Print Speed: 1.0 lps ± 20% [lps : lins per second]
Ribbon Cassette: Approx. 7 x 10 ³ lines (25°C continuous printing)

Options- Double-sided display

- Mounting bracket
- RS-232 interface



Weightronic Technology Ltd.

G/F., 34 Nam Cheong Street, Sham Shui Po, Kln., Hong Kong
 Tel : [852] 2381 8818 Fax: [852] 2391 9919
 E-mail: sales@weightronic.com
 Web Site: <http://www.weightronic.com> <http://www.磅.hk>